

Page 1/10

### Safety data sheet according to UK REACH

Printing date 25.06.2025 Version number: 1.06 Revision: 25.06.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier For industrial, professional & consumer use.
- · Trade name: MGC MKS2 Biocheck All Weather Masonry Paint All Colours
- · **UFI:** GVV4-70NM-4001-K7D2
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating
- · Application of the substance / the mixture Surface Coating
- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

Mould Growth Consultants Ltd. Unit A3 Longmead Business Centre Blenheim Road

Epsom Surrey KT19 9QQ

Tel: 01372 743334 Email: info@mgcltd.co.uk

- · Further information obtainable from: www.mgcltd.co.uk
- · 1.4 Emergency telephone number: +44 (0) 1372 743334 (business hours)

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02

GHS07

· Signal word Warning

(Contd. on page 2)

#### Trade name: MGC MKS2 Biocheck All Weather Masonry Paint All Colours

(Contd. of page 1)

### · Hazard-determining components of labelling:

2-octyl-2H-isothiazol-3-one

· Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

*P102 Keep out of reach of children.* 

*P103* Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

*Avoid breathing dust/fume/gas/mist/vapours/spray.* 

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:	H 1 1 CO CH II · II I·	> 10 250/	
EC number: 919-857-5 Reg.nr.: 01-2119463258-33-xxxx	Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	>10-≤25%	
Reg.mr.: 01-2119403230-33-xxxx	♦ Flam. Liq. 3, H226		
	♦ Asp. Tox. 1, H304		
	STOT SE 3, H336		
EC number: 918-668-5	Hydrocarbons, C9, aromatics	>2.5-\(\leq 10\)%	
Reg.nr.: 01-2119455851-35-xxxx	♠ Flam. Liq. 3, H226		
	<b>♦</b> Asp. Tox. 1, H304		
	Aquatic Chronic 2, H411		
	<u>♦</u> STOT SE 3, H335-H336		
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	>2.5-\(\leq 10\)	
EINECS: 203-603-9	♠ Flam. Liq. 3, H226		
Reg.nr.: 01-2119475791-29			
CAS: 330-54-1	3-(3,4-dichlorophenyl)-1,1-dimethylurea	≤1%	
EINECS: 206-354-4	<b>♦</b> Carc. 2, H351; STOT RE 2, H373		
Reg.nr.: 01-2119517622-45-0000/1			
	♦ Acute Tox. 4, H302		
CAS: 26530-20-1	2-octyl-2H-isothiazol-3-one	≤1%	
EINECS: 247-761-7	♠ Acute Tox. 3, H311		
Reg.nr.: 01-2120768921-45-0000/1			
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410		
	🔥 Skin Sens. 1A, H317		

(Contd. on page 3)

Trade name: MGC MKS2 Biocheck All Weather Masonry Paint All Colours

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and call for a doctor.

*In case of unconsciousness place patient stably in side position for transportation.* 

Supply fresh air; consult doctor in case of complaints.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately and show safety datasheet or label.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus

#### SECTION 6: Accidental release measures

### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/extraction at the workplace.

Prevent formation of aerosols.

Hygiene measures:

Wash hands before breaks and at the end of workday.

(Contd. on page 4)

*Printing date 25.06.2025 Version number: 1.06 Revision: 25.06.2025* 

Trade name: MGC MKS2 Biocheck All Weather Masonry Paint All Colours

(Contd. of page 3)

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage.
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed and in a well-ventilated place.

Keep away from heat.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics,

<2% aromatics

OEL Short-term value: 1200 mg/m<sup>3</sup>

Hydrocarbons, C9, aromatics

OEL Long-term value: 100 mg/m<sup>3</sup>

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm

Long-term value: 274 mg/m³, 50 ppm

Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

- $\cdot$  **Respiratory protection:** When spraying the product, use a respiratory protective device.
- Protection of hands:



Protective gloves

· Eye protection:



Tightly sealed goggles

GB

Printing date 25.06.2025 Version number: 1.06 Revision: 25.06.2025

Trade name: MGC MKS2 Biocheck All Weather Masonry Paint All Colours

(Contd. of page 4)

SECTION 9: Physical and chem	ical properties
9.1 Information on basic physical and o	chemical properties
General Information	
· Appearance:	ī· · · 1
Form:	Liquid
Colour:	Silver-coloured
· Odour:	Characteristic Not determined.
Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	e: 100 °C
Flash point:	40 °C
Flammability	Flammable.
· Auto-ignition temperature:	>230 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vape mixtures are possible.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	6.5 Vol %
Vapour pressure at 20 °C:	2 hPa
Density at 20 °C:	1.514 g/cm³
Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	NOT MISCIBLE
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	120 mPas
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	30.1 %
Water:	4.9 %
Solids content:	68.6%
9.2 Other information	No further relevant information available.

### SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available. 10.2 Chemical stability Stable under normal conditions

(Contd. on page 6)

Printing date 25.06.2025 Version number: 1.06 Revision: 25.06.2025

Trade name: MGC MKS2 Biocheck All Weather Masonry Paint All Colours

(Contd. of page 5)

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

No dangerous decomposition products when stored and handled correctly

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity:

Acute Fish toxicity

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

LC50 9.22 mg/l

Species: Oncorhynchus mykiss (rainbow trout)

Exposure duration: 96 h

Acute toxicity for daphnia

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

EC50 6.14 mg/l

Species: Daphnia magna (Water flea)

Exposure duration: 48 h

Acute toxicity for algae

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

ErC50 2.9 mg/l

Species: Pseudokirchneriella subcapitata (green algae)

Exposure duration: 72 h

Acute bacterial toxicity

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

EC50 1 - 10 mg/l

Ecotoxicology Assessment

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

(Contd. on page 7)

### Trade name: MGC MKS2 Biocheck All Weather Masonry Paint All Colours

(Contd. of page 6)

Chronic aquatic toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Data based on the safety data sheet (SDS) by the supplier.

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water danger class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

<b>SECTION</b>	11.	Tuesday and	 Course ations
			CO12111KONAKO111

· 14.1 UN-Number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
$\cdot ADR$	1263 PAINT RELATED MATERIAL
· IMDG	PAINT RELATED MATERIAL, MARINE POLLUTANT
$\cdot IATA$	PAINT RELATED MATERIAL

- · 14.3 Transport hazard class(es)
- · ADR, IATA



ClassLabel3 Flammable liquids.3

· IMDG



Class 3 Flammable liquids.

(Contd. on page 8)

*Printing date 25.06.2025 Version number: 1.06 Revision: 25.06.2025* 

Trade name: MGC MKS2 Biocheck All Weather Masonry Paint All Colours

	(Contd. of page
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substance
	Hydrocarbons, C9, aromatics
Marine pollutant:	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E,S-D
Stowage Category	A
14.7 Transport in bulk according to Annex II o	f
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
<b></b>	Maximum net quantity per outer packaging: 1000 ml
Transport category	<i>5</i>
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

OPOMION 15		•	•	•
SECTION 15:	<i>Romi</i>	atory in	tormat	On
DECITOR 13.	Mary Market	uivi v iii		uu

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· MAK (German Maximum Workplace Concentration)	
13463-67-7 titanium dioxide	<i>3A</i>
14807-96-6 Hydrated magnesium silicate	3B
14808-60-7 Quartz (SiO2)	1

· Poisons Act

· Regulated explosives precursors	
None of the ingredients is listed.	

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

(Contd. on page 9)

Printing date 25.06.2025 Version number: 1.06 Revision: 25.06.2025

Trade name: MGC MKS2 Biocheck All Weather Masonry Paint All Colours

(Contd. of page 8)

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
Wasser	4.9
NK	30.1

- · Waterhazard class: Water danger class 3 (Self-assessment): extremely hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Full text of H-Statements referred to under sections 2 and 3:

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1: Skin corrosion/irritation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

(Contd. on page 10)

Page 10/10

## Safety data sheet according to UK REACH

 Printing date 25.06.2025
 Version number: 1.06
 Revision: 25.06.2025

Trade name: MGC MKS2 Biocheck All Weather Masonry Paint All Colours

(Contd. of page 9)

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard — Category 3

\* Data compared to the previous version altered.

CD.