



HALOSTAIN TC

WATER BASED WOODSTAIN

- **RESISTANT TO ALGAE, LICHEN & MOSS GROWTH**
- **SOLVENT FREE**
- **EASY TO USE**
- **PROTECTIVE FINISH FOR NEW & OLD ROUGH SAWN TIMBER**



HALOSTAIN TC.....

.... Is a decorative and protective finish for exterior rough sawn timber such as Fencing, Garden Sheds and Cladding. It is resistant to moss, lichen and algae growth, easy to use and can be readily applied over old creosoted timbers, giving them new life.

DESCRIPTION

Composition: HALOSTAIN TC is a water based ready to use coating.

Appearance: Low odour, aqueous solution available in Deep Chestnut.

Performance: HALOSTAIN TC is a deep penetrating stain which provides water shedding and resistance to decay, algae and natural greying. HALOSTAIN TC provides a quick drying, easy to maintain decorative finish, with lasting colour and a life expectancy of up to 5 years.

Areas of use:

- Suitable for use on all above ground timbers.
- New and old fencing timbers and panels.
- Old creosoted timbers.
- New and old sheds.
- Exterior cladding, fascias, panelling and many more rough sawn timber features requiring stain.

Note: HALOSTAIN TC should NOT be used on below ground timbers.

Availability: Supplied in ready to use form in 5 litre containers in f- Deep Chestnut /

Deep Chestnut



Storage: Store in frost free conditions and keep airtight.

Coverage: HALOSTAIN TC will cover 5 to 12 square metres per litre for first coat and 12 to 20 square metres per litre for second coat. Coverages dependent on coarseness and porosity of timber.

SPECIFICATION

Preparation: Minimum preparation is required. Timbers should be stiff brushed free of dirt, algae etc. In extreme cases kill algal growths with LICHENITE, see separate leaflet. Avoid contaminating garden plants and the like.

Mixing: Thoroughly stir prior to application. Mix thoroughly before and periodically during use.

Application: Normally by brush but can be sprayed using low pressure spray (not airless) equipment. Note: When spraying, slightly extra dilution with water may be required.

Do not apply in wet or frosty conditions, or when there is a risk of same during drying. Application is preferable to dry timber, but slightly damp timbers can be treated successfully.

HALOSTAIN TC is re-coatable in 1-3 hours in normal drying conditions.

Plants & Animals: HALOSTAIN TC can be used in and around greenhouses and animal housing. Plants and animals may be re-introduced when coating is dry.

Cleaning: Clean equipment in water.

Shelf Life: 18 months in an unopened container.

Drying Time: 1-3 hours depending on conditions.



MOULD GROWTH CONSULTANTS LTD

Unit A3, Longmead Business Centre, Blenheim Road, Epsom, Surrey, KT19 9QQ

Tel: 01372 743334 Fax: 01372 720856

Website: <http://www.mgcltd.co.uk>

Email: info@mgcltd.co.uk