

MGC Quick Drying Stain Block

Seals Stains and prevents them from Bleeding through



- Touch Dry in 30 Minutes
- Low Odour
- Clean Brushes in Water
- Seals Problem Stains
- Water Based
- Quick Drying
- Excellent Adhesion
- Suitable for a Wide Range of Surfaces
- Clean Brushes and Equipment in Water
- Interior or Exterior Use

MGC Quick Drying Stain Block is a water based matt white blocking primer that has excellent adhesion to plaster, wood and previously painted surfaces. It will seal all stains preventing them from bleeding through and spoiling new decorations. When dry it can be decorated over with any type of paint, undercoat or wallpaper.



Seals all types of stains including:

- Bitumen
- Smoke Damage
- Nicotine
- Tide Marks
- Cooking Stains
- Crayon
- Graffiti
- Mould stains
- Soot
- Water stains

MGC Quick Drying Stain Block can also be used as a primer on porous surfaces, new plaster, new wood and MDF skirtings window cills etc.

PRODUCT DATA SHEET

PRODUCT	MGC Quick Drying Stain Block
Type	Water-based acrylic emulsion and stain inhibiting pigment to provide excellent stain-blocking properties.
Intended Use	As a stain block over a wide variety of surfaces. Not for use on damp surfaces. For interior and exterior use.
Special Features	Low odour, quick-drying with excellent hiding power. Wash brushes in water.
Preparation	Surfaces must be clean, dry and free from any grease or wax. Remove any unsound paint before applying stain blocker.
Application	STIR WELL BEFORE USE. Apply liberally and evenly with a synthetic brush or roller.
Coats	One coat is recommended but a second coat can be applied if staining is severe.
Drying Time	Touch dry in 30 minutes, depending on temperature and humidity.
Re-coating Time	Re-coat after 2 hours if necessary.
Application Temp.	Ideally 15 - 25°C, do not use below 10°C or in conditions of high humidity.
Coverage	Approximately 7sq.metres per litre per coat, depending on absorbency of the surface.
Maintenance	N/A
Compatibility	All types of paint and undercoats.
Settlement	STIR WELL BEFORE USE and ensure all sediment is mixed in.
Shelf-life/ Storage	Many years if stored in the original tightly closed container in a cool dry place.
Hazards	Non-flammable. Avoid contact with eyes, skin and clothing. In cases of contact with eyes, rinse immediately with plenty of water and seek medical attention. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Keep out of reach of children. A full Safety Data Sheet is available upon request or on www.mgcltd.co.uk
Clean-Up	With water whilst wet. If dried-on, clean equipment and brushes with Brush Restorer.
Sizes	2.5 Litres

Mould Growth Consultants Ltd.
Unit A3 Longmead Business Centre
Blenheim Road
Epsom KT19 9QQ

Telephone: 01372 743334

Email: info@mgcltd.co.uk

Web Site: www.mgcltd.co.uk